SAGOLAS

an Elcometer company

www.sagola.com











CLEAR

Versions: 1.2 - 1.2XL - 1.3 - 1.3XL Air consumption: 310 L/min Average paint output flow: 222 g/min Fan size: 285 - 305 mm Recommended pressure: 2.0 - 2.5 bar **Applications:** Clearcoats, Single Stage Paints, Basecoats, Industrial Bodyshop.



DVR AQUA

Versions: 1.2 - 1.2XL - 1.3 Air consumption: 280 L/min Average paint output flow: 227 g/min **Fan size:** 290 - 315 mm Recommended pressure: 1.5 - 2.0 bar Applications: Special for waterborne paints, high precision, high speed.



Versions: 1.2 - 1.3 - 1.3XL - 1.4 Air consumption: 465 L/min Average paint output flow: 198 g/min **Fan size:** 290 - 325 mm Recommended pressure: 1.8 - 2.0 bar **Applications:** Water and solvent-based basecoats, Clearcoats, high speed.



Versions: 1.2 - 1.2XL - 1.3 - 1.3XL - 1.4 Air consumption: 315 L/min Average paint output flow: 224 g/min **Fan size:** 285 - 300 mm Recommended pressure: 2.0 - 2.2 bar **Applications:** Clearcoats and HS Single stage Paints, high speed.

Passion for the red color

MAXIMUM EXPRESSION

Internal regulator version

> Digital version

Regulations

All SAGOLA products comply with the strictest safety standards for the manufacturing of painting equipment.

SAGOLA products comply with EC regulations and all the ATEX standards.

To protect itself against copies and counterfeits, SAGOLA registers the shape of its guns and naturally registers its trademark worldwide.

C E CA

EN 1953 ATEX $\langle \mathbf{E}_{\mathbf{x}} \rangle$ II 2G T60°C x LOM 05ATEX2091X **SQMDA 1151**

ES 2370348 559018 EP 1987886

With less travel and greater precision. Suitable for right and left handed.

New stainless steel guide box. Built in vernier for precise flow regulation.

Higher precision and smoothness.

High-precision pressure readings.

Protective ring in stainless steel

Rounder, more ergonomic and comfortable.



ATEX (Ex) II 2G Ex ia IIC T4

SQMDA 1136

Patents

3300029 201431059

Ultra-fine paint particle size and bigger spray

Unique in the market.

It avoids manipulation

and breakage

nozzles DV

High paint flow.

application.

Maximum speed of

Made of stainless steel.

of the glands.

New

Carried out at the tip of the air cap, it creates a finer and smoother spray.

(COLOR CODE). Perfect for differentiation spray guns when there are multiple painters.